





Transportation Assessment Report

Brooks Road Landfill Capacity Expansion Environmental Screening

2270386 Ontario Limited

April 1, 2024

Project name		Brooks Road Landfill Expansion					
Document title		Transportation Assessment Report Brooks Road Landfill Capacity Expansion Environmental Screening					
Project number		12561524					
File name		Brooks Road Landfill Capacity Expansion Environmental Screening Transportation Assessment Report-November 2023.docx					
Status Code	Revision	Author	Reviewer		Approved for issue		
			Name	Signature	Name	Signature	Date
S4	0	William Maria	Ryan Loveday		Blair Shoniker		4/1/2024

GHD

Contact: Axita Patel, Solid Waste Planner | GHD

65 Sunray Street,

Whitby, Ontario L1N 8Y3, Canada

T +1 905 686 6402 | F +1 905 432 7877 | E info-northamerica@ghd.com | ghd.com

© GHD 2024

This document is and shall remain the property of GHD. The document may only be used for the purpose for which it was commissioned and in accordance with the Terms of Engagement for the commission. Unauthorised use of this document in any form whatsoever is prohibited.

Contents

1.	Introduction	1
2.	Screening Criteria Checklist	5
3.	Existing Conditions	5
3.1	Methodology	5
3.1.1	Available Secondary Source Information Collection and Review	5
3.1.2	Process Undertaken	6
3.1.3	Field Investigations	6
3.1.4	Agency Consultation	6
3.2	Description of Existing Conditions	6
	2022 Base Traffic Conditions	6
4.	Potential Effects, Mitigation Measures & Net Effects	9
4.1	Description of Project Components and Activities	9
4.2	Methodology and Investigations	10
4.3	Future Transportation Conditions	10
4.3.1	Methodology	10
	Horizon Year 10	
	Background Volume Growth Rate	11
	Future Traffic Volumes	11
4.3.2	Capacity Analysis	12
4.3.3	Safety Analysis	13
	4.3.3.1 Collision Analysis	13
	4.3.3.2 Sight Line Analysis	13
4.4	Transportation Net Effects	13
4.4.1	Potential Effects on Transportation Environment	14
4.5	Mitigation Measures	14
4.5.1	Net Effects	14
4.6	Monitoring Requirements	14
4.7	Additional Approvals	14
5.	Conclusion	14

Table index

Table 2.1	Screening Criteria Checklist – Transportation	5
Table 3.1	Existing Capacity Analysis	8
Table 4.1	Summary of Proposed Brooks Road Landfill Capacity Expansion Design vs Existing Landfill	9
Table 4.2	2026Future Conditions Capacity Analysis at Peak Operations	13

Figure index

Figure 1.1	Location of the Proposed Undertaking	1
Figure 1.2	Proposed Capacity Expansion Concept	2
Figure 1.3	Transportation Study Areas	4
Figure 3.1	2022 Existing Peak Hour Volumes	7
Figure 4.1	2026 Future Total Peak Hour Volumes	12

Appendices

Appendix A	Detailed Turning Movement Data Sheets and Synchro Capacity Reports
------------	--

1. Introduction

The Brooks Road Landfill Site (Site) is located at 160 Brooks Road, near Cayuga, Haldimand County, Ontario and is owned and operated by 2270386 Ontario Limited, herein referred to as Brooks Road Environmental (BRE, Owner, Proponent). The location of the Site is shown in Figure 1.1.




Figure 1.1 Location of the Proposed Undertaking

The Site, which operates under Environmental Compliance Approval (ECA) No. A110302 (Landfill ECA), has an approved annual fill rate of 250,000 tonnes per year and a total capacity of 1,045,065 cubic metres (m³) (including waste and cover). The Site also operates under an air and noise ECA No. 7323-C6EJUM (Air ECA) and industrial sewage works ECA No. 1122-BKUPSM (Industrial Sewage ECA). The Site has accepted waste (in one form or another) since 1959 and received a Certificate of Approval (CofA, now referred to as an ECA) in 1980, with amendments approved by the Ministry of the Environment (currently the Ministry of Environment, Conservation and Parks (MECP) in 1980, 2002, 2004, 2005, 2007, 2011, 2012, 2013, 2014, 2017, 2018, 2020, and 2021. Under the current ECA, the Site is licenced to receive post-diversion solid non-hazardous Industrial, Commercial & Institutional (IC&I) waste from across Ontario. The 14.3-hectare (ha) Site contains an approved fill area of 6 ha.

In 2018, BRE completed an Individual Environmental Assessment (EA) to increase the total approved capacity at the site to allow for the continued receipt of post-diversion IC&I waste over a five-to-seven-year planning period and an amendment to the Site's rate of fill to provide for a maximum of 151,000 tonnes per year (known as the Brooks Road

Landfill Vertical Capacity Expansion EA). The Brooks Road Landfill Vertical Capacity Expansion EA was approved by the Minister of Environment, Conservation and Parks on January 15, 2019. The Site ECA was amended in 2021 to increase the annual rate of fill from 151,000 tonnes per year to a maximum of 250,000 tonnes per year, which is proportional to the daily maximum of 1,000 tonnes per day. The 2021 ECA amendment was subject to the Environmental Screening Process.

In order to meet the growing demand from waste generators and customer for a safe and reliable waste management facility for their post diversion solid non-hazardous Industrial, Commercial & Institutional waste (including impacted soils), Brooks Road Environmental is proposing to expand the capacity of the Brooks Road Landfill by approximately 219,400 m³, adding capacity equal to approximately two additional years. This expansion would be achieved through a combination of re-engineering the Site's final contours to expand the Site vertically in the expansion area (not to exceed current approved peak contours), as well as increasing the existing landfill footprint to expand the Site horizontally, as shown in Figure 1.2.




Figure 1.2 Proposed Capacity Expansion Concept

The proposed expansion would amend the approved ECA to allow for landfill volume expansion by approximately 219,400 m³, allowing for receipt of an approved maximum daily quantity (1,000 tonnes per day) throughout the year, maintaining the approved rate of 250,000 tonnes per year. The proposed change to the total landfill capacity requires additional landfill infrastructure and changes to the currently approved landfill volume, footprint, and final contours.

The proposed Brooks Road Landfill Site capacity expansion is subject to the Environmental Screening Process in accordance with Section 13 of Ontario Regulation 101/07 – Waste Management Projects Regulation of the Ontario *EA Act*, as follows:

A change to a landfilling site or dump is defined as a major commercial or business enterprise or activity and is designated as an undertaking to which the Act applies, if the changes meet the following criteria:

- 1. The total waste disposal volume of the landfilling site or dump after the change would exceed the total waste disposal volume that the landfilling site or dump was authorized to have under the Environmental Protection Act before the change by more than 100,000 cubic metres but by less than or equal to 375,000 cubic metres.*
- 2. The increase in the total waste disposal volume of the landfilling site or dump would not exceed 25 per cent of the total waste disposal volume that the landfilling site or dump was authorized to have under the Environmental Protection Act before the change.*
- 3. If a notice of completion under the Environmental Screening Process for Waste Management Projects has been submitted to the Ministry in respect of a previous change to the landfilling site or dump that meets the criteria in paragraphs 1 and 2, the day on which the notice of commencement is issued under the Environmental Screening Process for Waste Management Projects in respect of the change is at least 10 years after the day the notice of completion in respect of the previous change was submitted.*

Section 13 of Ontario Regulation 101/07 – Waste Management Projects Regulation exempts this Project from Part II of the *EA Act*, subject to fulfilling the Environmental Screening process. The Screening will be conducted in accordance with the planning and design process outlined in MECP “*Guide to Environmental Assessment Requirements for Waste Management Projects*.” The Environmental Screening Process includes identifying and applying screening criteria to determine and describe potential environmental effects, public/external agency consultation, and the development of measures to mitigate identified environmental effects. The results of the Study will be documented in an Environmental Screening Report, which will be released for review to Stakeholders including Indigenous communities, the public, and government agencies. Upon completion of the Environmental Screening Process an application will be made to amend the existing ECA No. A110302.

GHD has prepared a Transportation Assessment on behalf of BRE for the proposed undertaking. This report documents the following as it relates to the transportation environment:

- Baseline/existing conditions (i.e., what exists in the absence of the proposed project).
- Potential effects on the environment, mitigation measures, and net effects.
- Future monitoring requirements to be implemented.

The Study Areas reviewed for the transportation assessment were as follows (see **Figure 1.3**):

- **Site Study Area (SSA)** – the 14.3 ha area within the existing, approved boundaries of the Site, as defined by ECA No. A110302, as amended; and
- **Local Study Area (LSA)** – the area within the vicinity of the Site extending approximately 1 kilometre (km) in all directions.



Legend

- Site Study Area
- Local Study Area (1km Radius)

<p>Paper Size ANSI B</p> <p>0 75 150 225 300</p> <p style="text-align: center;">Meters</p> <p>Map Projection: Transverse Mercator Horizontal Datum: North American 1983 Grid: NAD 1983 UTM Zone 17N</p>	<p>N</p>		<p>BROOKS ROAD LANDFILL 160 BROOKS ROAD, CAYUGA, ONTARIO TRANSPORTATION ASSESSMENT REPORT</p>	<p>Project No. 12561524 Revision No. - Date Oct 26, 2022</p>
STUDY AREAS			FIGURE 1.3	

Q:\GIS\PROJECTS\12561000e\12561524\Layouts\202210_SurfaceWater\12561524_202210_SurfaceWater_GIS001.mxd
Print date: 26 Oct 2022 - 13:27

Data source: Google Earth Imagery, Date: 07/08/2018

2. Screening Criteria Checklist

At the beginning of the Environmental Screening, the Screening Criteria Checklist (provided as Schedule I, pp 67 – 69, to the “Guide to Environmental Assessment Requirements for Waste Management Projects”) is to be completed based on the information provided in the Project Description. The Screening Criteria reflect the broad definition of “environment” contained in the *Ontario Environmental Assessment Act*.

As noted in the Guide:

*“The Screening Criteria are presented in the form of a checklist with the option of a “Yes” or “No” response. Mitigation measures **are not** to be considered in concluding whether there is “No” potential environmental effect. That is, the proponent is required to answer “Yes” even if the proponent believes that a potential environmental effect could likely be mitigated. The reason for requiring a “Yes” is to ensure that mitigation measures are open to discussion and review. Another reason for this approach is that further discussion and review of a potential effect may reveal that there is no actual effect, in which case no mitigation is required. Where a “yes” has been identified, the proponent is to provide additional information in the Environmental Screening Report, explaining the potential effect(s), methods to mitigate or address the effect(s), any net effects that are anticipated and if so, their significance. Even where the proponent indicates that no environmental effects are anticipated, it is recommended that additional information is provided in the Environmental Screening Report in order to support the “no effects” conclusion.”*

Each criterion is based on a question which is prefaced with the phrase, “*Might the Project...*” Table 2.1 was completed as the first step of the Environmental Screening Process and is a summary of the criteria for the Transportation discipline. Further descriptions of the criteria for which a “Yes” response was indicated in the Screening table are discussed in Section 4 of this report.

Table 2.1 Screening Criteria Checklist – Transportation

	Criterion	YES	NO	Additional Information
	Might the project...			
1. Socio-Economic				
6.8	Cause negative effects related to traffic?	X		The proposed landfill expansion would result in changes to the existing landfill footprint, cover design (daily, intermediate, final), final contours, and on-site operations and may cause negative effects related to traffic through prolonging the life of the Site.

3. Existing Conditions

The following subsections describe the existing conditions that are found within the SSA and LSA of the proposed project.

3.1 Methodology

3.1.1 Available Secondary Source Information Collection and Review

Available secondary sources of information were collected and reviewed by the Transportation Study Team to determine existing Transportation conditions within the Study Area(s). The following sources of secondary information were collected and reviewed in completing the 2018 Individual Environmental Assessment:

- Haldimand County Annual Average Daily Traffic (AADT) data, 2005

– Haldimand County Annual AADT data, 2011

3.1.2 Process Undertaken

Information on the Transportation Existing Conditions within the Study Area was gathered from a combination of secondary source research, field investigations and discussions with Haldimand County staff.

3.1.3 Field Investigations

As part of the 2018 Individual Environmental Assessment, turning movement counts were conducted at the intersection of Highway 3 and Brooks Road and at the existing Brooks Road Landfill Site driveway during the weekday a.m., mid-day and p.m. peak periods and Saturday mid-day peak periods. These counts were completed on Saturday, December 5, 2015 and on Monday, December 7, 2015.

3.1.4 Agency Consultation

Also, as part of the 2018 Individual Environmental Assessment, discussions with Haldimand County staff took place in December 2015 to confirm AADT data.

3.2 Description of Existing Conditions

Road Network

The following two major roads provide access to the existing Brooks Landfill:

Highway 3 (Talbot Road) – within the vicinity of Brooks Road, Highway 3 (Talbot Road) is a two-lane road with a posted speed limit of 80 kph. The intersection of Highway 3 and Brooks Road is stop controlled on Brooks Road with both eastbound and westbound right turn taper on Highway 3.

Brooks Road – Brooks Road is a two-lane road that extends from Highway 3 (Talbot Road) in the south and terminates at Indiana Road to the north. The speed limit on this road is 50 kph. Brooks Road is paved from Highway 3 to just north of the Brooks landfill driveway access where it changes to a gravel road for the remaining length to Indiana Road.

Traffic Data

Historical AADT data was obtained from Haldimand County. The 2005 AADT on Brooks Road approximately 500 metres north of Highway 3 was 144 two-way trips. In 2011 the AADT was slightly lower at 114 two-way trips. Discussions with staff confirmed that the split is approximately 50/50 between north and south volumes.

Turning movement counts were also conducted on Saturday, December 5, 2015 and on Monday, December 7, 2015 at both the intersection of Highway 3 and Brooks Road and at the existing Brooks Road Landfill Site driveway during the weekday a.m., mid-day and p.m. peak periods and Saturday mid-day peak periods. Detailed turning movement data sheets are found in Appendix A.

2022 Base Traffic Conditions

To establish the base 2022 traffic conditions and capture any expected background growth in traffic volumes at the study area intersections, a conservative compound annual growth rate of 2.0 percent was adopted and utilized to forecast grow the 2015 turning movement counts to 2022. The base 2022 traffic volumes also includes the estimated 16 site trucks per day as a result of the proposed vertical expansion approved in 2018. To provide a conservative and worst-case scenario analysis, all 16 of the daily truck trips associated with the vertical expansion were applied to each peak hour (i.e., all 16 would enter/exit the site within each of the peak hours which results in a large over estimation of the daily traffic volumes to the Site).

The resulting 2022 weekday a.m., mid-day and p.m. peak hour as well as the Saturday peak hour volumes are summarized in Figure 3.1.




Figure 3.1 2022 Existing Peak Hour Volumes

Traffic on Brooks Road is predominately truck traffic specific to the landfill operation, traffic on Highway 3 is a mix of both commuter and truck traffic.

Landfill Operations

The Brooks Road Landfill Site is currently open and accepting waste during the week and on Saturdays. The site currently handles 1,000 tonnes of material per day based on the following five different truck configurations:

- Walking floor – can handle 25 to 40 metric tonnes per load
- Roll-off – can handle 0.5 to 10 metric tonnes per load
- Front End – can handle 3 to 12 metric tonnes per load
- Tri-axle – can handle 14 to 22 metric tonnes per load
- Dump trailer – can handle 34 to 42 metric tonnes per load

The current maximum daily truck traffic at the landfill assuming delivery of 1,000 tonnes of material per day is 16 to 24 walking floor trucks, 2 to 4 front end trucks and 2 to 6 roll-offs for a total of 34 inbound and 34 outbound trucks plus another one or two trips for staff over the period of a day. This number can increase slightly if there are certain soil jobs on the site as the walking floor trucks are replaced with Dump trailers and Tri-axle trucks.

The turning movement counts conducted at the site driveway on Saturday December 5, 2015 and Monday December 7, 2015 show the following total volume of trucks entering and exiting the landfill during the peak hours:

- Weekday am peak hour – 12 inbound and 11 outbound
- Weekday mid-day peak hour – 12 inbound and 13 outbound
- Weekday pm peak hour – 10 inbound and 13 outbound
- Saturday mid-day peak hour – 16 inbound and 14 outbound

The traffic volumes confirm that the peak operating times for the landfill occur during both the weekday and Saturday mid-day peak hours when the maximum volumes of inbound and outbound traffic were observed.

Coincidentally, a review of the 2015 traffic counts confirms that the volume of inbound and outbound traffic from the landfill during the two survey dates was considerably higher than the typically expected volumes provided by the operator assuming delivery of 1,000 tonnes of material per day. It was confirmed that during the two survey dates, there was a transfer of clean clay to another property that resulted in approximately 75 additional loads throughout both days.

As a result, the analysis of the existing 2022 conditions not only includes the approved vertical expansion but also includes additional traffic that is not typical for existing operations and results in slightly reduced capacity at both the site driveway on Brooks Road and at the intersection of Brooks Road and Highway 3.

Capacity Analysis

As a measure of the existing capacity on the adjacent road network surrounding the Brooks Landfill, both the site access on Brooks Road and the stop-controlled intersection of Brooks Road and Highway 3 were analyzed using the projected 2022 turning movement volumes for the weekday am, mid-day, pm and Saturday peak hours. A summary of the capacity analysis using Synchro version 10 is summarized in Table 3.1 below with detailed reports provided in Appendix A.

Table 3.1 Existing Capacity Analysis

Intersection	Movement v/c ratio (LOS) delay			
	A.M. Peak	Mid-Day Peak	P.M. Peak	Sat Peak
Brooks Road and Landfill access	WBLR = 0.03 LOS A 9 Sec NBTR = 0.02 LOS A 0 Sec SBTL = 0 LOS A 0 Sec	WBLR = 0.03 LOS A 9 Sec NBTR = 0.02 LOS A 0 Sec SBTL = 0 LOS A 0 Sec	WBLR = 0.03 LOS A 9 Sec NBTR = 0.02 LOS A 0 Sec SBTL = 0 LOS A 0 Sec	WBLR = 0.03 LOS A 9 Sec NBTR = 0.02 LOS A 0 Sec SBTL = 0 LOS A 0 Sec
Brooks Road and Highway 3	EBTLR = 0 LOS A 0 Sec WBTLR = 0 LOS A 0 Sec NBTLR = 0 LOS B 11 Sec SBTLR = 0.05 LOS B 10 Sec	EBTLR = 0 LOS A 0 Sec WBTLR = 0 LOS A 0 Sec NBTLR = 0 LOS B 11 Sec SBTLR = 0.05 LOS B 11 Sec	EBTLR = 0 LOS A 0 Sec WBTLR = 0 LOS A 0 Sec NBTLR = 0 LOS B 12 Sec SBTLR = 0.06 LOS B 12 Sec	EBTLR = 0.01 LOS A 0 Sec WBTLR = 0 LOS A 0 Sec NBTLR = 0 LOS A 0 Sec SBTLR = 0.07 LOS B 12 Sec

The turning movements at both study intersections currently operate with levels of service ‘B’ or better during the weekday am, mid-day, pm and Saturday mid-day peak hours.

The analysis of existing conditions confirms no current capacity constraints at either study intersection despite the higher than normal traffic volumes captured during the survey of existing traffic volumes as a result of the movement of clean clay off-site.

Safety Analysis

Collision Analysis

A review of available data shows that there is no indication that either Highway 3 in the vicinity of Brooks Road, or Brooks Road north to the site has experienced significantly higher collision frequency than the historical average accident rate along Highway 3 in Haldimand County.

Sight Line Analysis

The site entrance in its current location satisfies the sight distance requirements for trucks approaching and departing from the site. Brooks Road is fairly straight with little deviation in the horizontal or vertical alignment. Existing sight distances are in excess of 350 metres both to the north and south of the driveway access which exceeds the required sight distance based on TACC standard of 85 metres for stopping sight distance which for a posted speed limit of 50 kph (60 kph design speed).

4. Potential Effects, Mitigation Measures & Net Effects

A Project Description, which includes proposed engineering design figures, was prepared so that potential environmental effects and mitigation measures could be identified. The following subsections provide a general summary of the proposed undertaking.

4.1 Description of Project Components and Activities

The project for which the Environmental Screening Process is being undertaken is a proposed capacity expansion of 219,400 m³ and involves a change to the final site capacity, contours, and footprint. Some level of construction is required to implement the proposal. This would be a combination of re-engineering the Site's final contours to expand the Site vertically in the expansion area (not to exceed current approved peak contours, as well as increasing the existing landfill footprint to expand the Site horizontally. Modification to the northern perimeter access road and stormwater drainage ditch would be required to accommodate the proposed changes to the final Site contours. The former railway property would continue to provide buffer land for the Site. The Brooks Road Landfill will continue to operate within currently approved operating hours and current construction activities and daily operations will continue as usual. There are no changes to the annual fill rate limits (maximum 1,000 tonnes per day and 250,000 tonnes per year) proposed as part of this project.

A summary of the key elements of the proposed capacity expansion compared to the existing approved Site is provided in Table 4.1.

Table 4.1 Summary of Proposed Brooks Road Landfill Capacity Expansion Design vs Existing Landfill

Design Component	Existing Landfill	Proposed Capacity Expansion
Volume (m ³)	1,045,065	1,264,4651
Footprint Area (ha)	6.07	7.15
Peak Elevation (mAMSL) (top of final cover)	221.50	225.66
Peak Elevation – top of waste (mAMSL)	220.75	224.91
Crest of Slope Elevation (mAMSL)	221.0	225.30

Design Component	Existing Landfill	Proposed Capacity Expansion
Slopes (Top/Sides)	Top – 20:1 (5%) Sides – 4:1 (25%)	Top – 20:1 (5%) Sides – 4:1 (25%) New stage is 4:1 (25%) north side slope, extends to a new peak elevation (i.e., elevated 20:1 [5%] plateau), and the south side slope (25%) ties-in to existing approved top of waste plateau. All other sides remain the same.
Stormwater Pond	Permanent pool – 1,266 m ³ Total live storage – >5,502 m ³	Pond capacity is sufficient for the proposed expansion based on existing Stormwater Management Plan.
Stormwater Drainage Ditch		Stormwater drainage ditch shifted by 30 m. East and west ditches will extend to maintain full perimeter ditch.
Perimeter Roads		Northern perimeter access road shifted by 29 m. East access road extended as appropriate. Access road will extend west, proposed to connect to Brooks Road as a secondary site access (locked during normal operation). A turnaround area will be provided in the northwest corner.
Maximum Daily Truck Traffic	25 to 50	25 to 50
Post-Closure Leachate Generation Rate	33 m ³ /day	39 m ³ /day
Capacity anticipated to be reached (year)	2024	2026

4.2 Methodology and Investigations

The assessment of effects associated with the proposed undertaking was carried out through a series of steps that is based, in part, on the description of existing conditions as well as the Project Description and Site Plan. The assessment of effects was also undertaken within the context of the previously completed Screening Criteria Checklist, as summarized in **Section 2** of this report.

Based on the description of the Alternative Methods provided in **Section 2** and the characterization of Transportation Existing Conditions within the Study Area described in **Section 3**, the following section provides the Transportation Future Conditions within the Study Area and any recommended mitigation measures for the 2026 horizon year when the Site is anticipated to reach capacity. The future conditions traffic analysis utilizes the existing 2022 conditions as a baseline and incorporates additional corridor growth to the traffic volumes.

As previously presented in **Table 4.1**, the maximum daily truck traffic before and after the proposed capacity expansion does not change and remains at 25 to 50 trucks per day. As a result, the turning volumes entering and exiting the site access are not expected to change from exiting conditions.

4.3 Future Transportation Conditions

4.3.1 Methodology

Horizon Year

The proposed capacity expansion for the existing site is expected to extend the life of the landfill by one approximately two years from 2024 to 2026. Therefore, a future horizon year of 2026 has been assumed representing the worst-case

scenario which includes the anticipated corridor growth expected until the Site reaches capacity. Haldimand County's Traffic Impact Study Guidelines for developments generating less than 500 peak hour vehicle trips requires future conditions traffic analysis be conducted for both the opening year and 5 years after opening. However, post 2026, the Site will generate no traffic onto the surrounding road network and therefore, analysis of future conditions was limited to the 2026 horizon year.

Background Volume Growth Rate

In order to capture any expected background growth in traffic volumes at the study area intersections, a conservative compound annual growth rate of 2.0 percent has been adopted and will be utilized to forecast for the 2026 traffic volumes.

Future Traffic Volumes

The Forecasted 2026 turning movement counts were projected at both the intersection of Highway 3 and Brooks Road and at the existing Brooks Road Landfill Site driveway during the weekday a.m., mid-day and p.m. peak periods and Saturday mid-day peak periods. This includes the existing truck traffic corresponding to approximately 1,000 tonnes per day. As previously noted, to provide a conservative and worst-case scenario analysis, the daily truck trips associated with the Site were applied to each peak hour (i.e., the total amount of daily truck trips would enter/exit the site within each of the peak hours). The resulting weekday a.m., mid-day and p.m. peak hour as well as the Saturday peak hour volumes are summarized in Figure 4.1. No additional site trips were accounted for in the 2026 horizon year as the maximum daily number of trucks generated by the Site remains at 25 to 50 trucks after the proposed capacity expansion.




Figure 4.1 2026 Future Total Peak Hour Volumes

4.3.2 Capacity Analysis

As a measure of the capacity on the adjacent road network surrounding the Brooks Road Landfill at peak operations (i.e., 1,000 tonnes of material per day translating to 25 to 50 daily trucks), both the Site access on Brooks Road and the stop-controlled intersection of Brooks Road and Highway 3 were analyzed using the projected 2026 peak turning movement volumes for the weekday a.m., mid-day, p.m. and Saturday peak hours. A summary of the capacity analysis using Synchro version 10 is summarized in the Table 4.2 with detailed reports provided in Appendix A.

Table 4.2 2026 Future Conditions Capacity Analysis at Peak Operations

Intersection	Movement v/c ratio (LOS) delay			
	A.M. Peak	Mid-Day Peak	P.M. Peak	Sat Peak
Brooks Road & Brooks Road Landfill Site access	WBLR = 0.03 LOS A 9 SEC NBTR = 0.02 LOS A 0 SEC SBTL = 0 LOS A 0	WBLR = 0.03 LOS A 9 SEC NBTR = 0.02 LOS A 0 SEC SBTL = 0 LOS A 0 SEC	WBLR = 0.03 LOS A 9 SEC NBTR = 0.02 LOS A 0 SEC SBTL = 0 LOS A 0 SEC	WBLR = 0.03 LOS A 9 SEC NBTR = 0.02 LOS A 0 SEC SBTL = 0 LOS A 0 SEC
Brooks Road & Highway 3	EBTLR = 0 LOS A 0 SEC WBTLR = 0 LOS A 0 SEC NBTLR = 0 LOS B 11 SEC SBTLR = 0.06 LOS B 11 SEC	EBTLR = 0 LOS A 0 SEC WBTLR = 0 LOS A 0 SEC NBTLR = 0 LOS B 11 SEC SBTLR = 0.05 LOS B 11 SEC	EBTLR = 0 LOS A 0 SEC WBTLR = 0 LOS A 0 SEC NBTLR = 0 LOS B 12 SEC SBTLR = 0.06 LOS B 12 SEC	EBTLR = 0.01 LOS A 0 SEC WBTLR = 0 LOS A 0 SEC NBTLR = 0 LOS A 0 SEC SBTLR = 0.08 LOS B 12 SEC

Both intersections overall are expected to operate with minimal delay and substantial excess capacity under future 2026 conditions. Individual movements at both study intersections are expected to operate with levels of service ‘B’ or better representing minimal delay, and volume-to-capacity (v/c) ratios not exceeding 0.08 representing substantial excess capacity, during the weekday a.m., mid-day, p.m. and Saturday mid-day peak hours.

The analysis of future 2026 conditions under peak operations confirms no vehicle delay issues or capacity constraints at either study intersection resulting from the proposed capacity expansion.

4.3.3 Safety Analysis

4.3.3.1 Collision Analysis

Existing conditions collision analysis determined no indication that either Highway 3 in the vicinity of Brooks Road or Brooks Road north to the site has experienced significantly higher collision frequency than the historical average accident rate along Highway 3 in Haldimand County. Since no additional site traffic is generated by the proposed capacity expansion, safety conditions remain unchanged.

4.3.3.2 Sight Line Analysis

Existing conditions sight line analysis determined the site entrance in its current location satisfies the sight distance requirements for trucks approaching and departing from the site.

4.4 Transportation Net Effects

This Section provides an assessment of the potential negative environmental effects (i.e., those for which a “Yes” answer was given in the Screening Criteria Checklist) for those Transportation criteria which might be affected by the project as identified in **Section 2**. The effects assessment describes how existing environmental conditions in the Study Area(s) would change as a result of the construction and operation of the proposed undertaking.

As described in Section 2, a “Yes” was applied to the following Transportation criteria:

6. Socio-Economic			
6.8	Cause negative effects related to traffic?	X	The proposed landfill expansion would result in changes to the existing landfill footprint, cover design (daily, intermediate, final), final contours, and on-site operations and may cause negative effects related to traffic through prolonging the life of the Site.

With respect to the above criterion, a description of the potential negative environmental effects, necessary mitigation measures and the resultant net effects on the environment are discussed. Studies conducted during the Environmental Screening Process showed that the anticipated effects will be much less than expected or will not occur at all. In all cases, impact management (mitigation) measures have been identified that, when applied, will eliminate the potential environmental effects, or reduce them to acceptable levels.

4.4.1 Potential Effects on Transportation Environment

Based on the Future Conditions traffic analysis undertaken in **Section 4.1**, it is expected that the proposed capacity expansion will have a negligible transportation effect at the study area intersections and surrounding road network. Truck traffic associated with the proposed capacity expansion will not contribute any additional truck traffic within the study area, therefore it is not expected to adversely affect residents, businesses, institutions and movement of farm vehicles in the LSA.

4.5 Mitigation Measures

With no additional truck traffic generated by the proposed capacity expansion, no mitigation measures are recommended in order to avoid or minimize impacts on Transportation.

4.5.1 Net Effects

As no mitigation measures beyond those incorporated into the design are recommended, the net impacts of the capacity expansion from a transportation perspective are represented in the Future Transportation Conditions analysis undertaken in Section 4.1.

4.6 Monitoring Requirements

Since no mitigation measures were identified in **Section 4.5** are implemented as envisioned, no further monitoring of the transportation effects are recommended.

4.7 Additional Approvals

No additional approvals are required for transportation.

5. Conclusion

Under existing 2022 traffic conditions the site is expected to be acceptable from a traffic operations and safety perspective. The capacity analysis under peak operations confirms no current capacity constraints in the LSA road network. Concerning safety, a review of previously obtained data shows the LSA road network has not experienced significantly higher collision frequency than the local historical average accident rate, and a review of the site entrance in its current location satisfies the sight distance requirements.

The analysis of future conditions undertaken for the 2026 horizon year when the Site is anticipated to reach maximum capacity, indicates the site will continue to be acceptable from a traffic operations and safety perspective. Under peak operations no vehicle delay issues or capacity constraints at either study intersection are expected. Concerning safety, it is expected that since no additional site traffic is generated by the proposed capacity expansion, existing safety conditions will not deteriorate, and Site traffic will continue to be safely accommodated by the existing site entrance.

No mitigation measures beyond those incorporated into the design have been recommended as a result of the proposed capacity expansion.

Concerning the truck transportation effects along access roads, no effects are expected. With no additional traffic being generated by the Site, there is an expected minimal impact on traffic safety, traffic operations, and no potential road improvements are required or recommended.

Appendices

Appendix A

**Detailed Turning Movement Data Sheets
and Synchro Capacity Reports**

Ontario Traffic Inc

Morning Peak Diagram

Specified Period

From: 8:30:00
To: 10:30:00

One Hour Peak

From: 9:30:00
To: 10:30:00

Municipality: Cayuga
Site #: 1533100001
Intersection: Talbot Rd & Brook Rd
TFR File #: 1
Count date: 5-Dec-15

Weather conditions:
Person(s) who counted:

**** Non-Signalized Intersection ****

Major Road: Talbot Rd runs W/E

North Leg Total: 7
North Entering: 3
North Peds: 0
Peds Cross: \times

Heavys	0	0	0	0
Trucks	0	0	0	0
Cars	2	0	1	3
Totals	2	0	1	



Heavys	0
Trucks	0
Cars	4
Totals	4

East Leg Total: 276
East Entering: 130
East Peds: 0
Peds Cross: \times

Heavys	0
Trucks	5
Cars	127
Totals	132




Brook Rd


Cars	1	0	0	1
Trucks	124	5	0	129
Heavys	0	0	0	0
Totals	125	5	0	



Talbot Rd



Heavys	0
Trucks	0
Cars	3
Totals	3
Heavys	0
Trucks	6
Cars	139
Totals	145
Heavys	0
Trucks	0
Cars	2
Totals	2
Heavys	0
Trucks	6
Cars	144
Totals	



Talbot Rd



Cars	140	6	0	146
Trucks				
Heavys				
Totals				

Peds Cross: \times
West Peds: 0
West Entering: 150
West Leg Total: 282

Cars	2
Trucks	0
Heavys	0
Totals	2



Cars	1	0	0	1
Trucks	0	0	0	0
Heavys	0	0	0	0
Totals	1	0	0	

Peds Cross: \times
South Peds: 0
South Entering: 1
South Leg Total: 3

Comments

Ontario Traffic Inc

Mid-day Peak Diagram

Specified Period

From: 11:30:00

To: 14:30:00

One Hour Peak

From: 11:30:00

To: 12:30:00

Municipality: Cayuga
Site #: 1533100001
Intersection: Talbot Rd & Brook Rd
TFR File #: 1
Count date: 5-Dec-15

Weather conditions:
Person(s) who counted:

**** Non-Signalized Intersection ****

Major Road: Talbot Rd runs W/E

North Leg Total: 36
 North Entering: 18
 North Peds: 0
 Peds Cross: \times

Heavys	0	0	0	0
Trucks	0	0	12	12
Cars	4	0	2	6
Totals	4	0	14	



Heavys	0
Trucks	12
Cars	6
Totals	18

East Leg Total: 343
 East Entering: 171
 East Peds: 0
 Peds Cross: \times

Heavys	0
Trucks	9
Cars	151
Totals	160




Brook Rd


Cars	3	12	0	15
Trucks	147	9	0	156
Heavys	0	0	0	0
Totals	150	21	0	



Talbot Rd



Heavys	0
Trucks	0
Cars	3
Totals	3
Heavys	0
Trucks	6
Cars	152
Totals	158
Heavys	0
Trucks	0
Cars	3
Totals	3
Heavys	0
Trucks	6
Cars	158
Totals	164



Talbot Rd



Peds Cross: \times
 West Peds: 0
 West Entering: 164
 West Leg Total: 324

Cars	3
Trucks	0
Heavys	0
Totals	3



McFarlane Rd

Cars	0	0	0	0
Trucks	0	0	0	0
Heavys	0	0	0	0
Totals	0	0	0	



Peds Cross: \times
 South Peds: 0
 South Entering: 0
 South Leg Total: 3

Comments

Ontario Traffic Inc

Total Count Diagram

Municipality: Cayuga
Site #: 1533100001
Intersection: Talbot Rd & Brook Rd
TFR File #: 1
Count date: 5-Dec-15

Weather conditions:
Person(s) who counted:

**** Non-Signalized Intersection ****

Major Road: Talbot Rd runs W/E

North Leg Total: 109
 North Entering: 56
 North Peds: 0
 Peds Cross: \times

Heavys	0	0	0	0
Trucks	0	0	37	37
Cars	8	1	10	19
Totals	8	1	47	



Heavys	0
Trucks	38
Cars	15
Totals	53

East Leg Total: 1401
 East Entering: 687
 East Peds: 0
 Peds Cross: \times

Heavys	0
Trucks	26
Cars	626
Totals	652




Brook Rd


Cars	7	38	0	45
Trucks	614	26	0	640
Heavys	2	0	0	2
Totals	623	64	0	



Talbot Rd



Heavys	0
Trucks	0
Cars	8
Totals	8
Heavys	0
Trucks	19
Cars	648
Totals	667
Heavys	0
Trucks	0
Cars	14
Totals	14
Heavys	0
Trucks	19
Cars	670
Totals	670



Talbot Rd



McFarlane Rd



Cars	658	56	0	714
Trucks				
Heavys				
Totals	714			

Peds Cross: \times
 West Peds: 0
 West Entering: 689
 West Leg Total: 1341

Cars	17
Trucks	0
Heavys	0
Totals	17



Cars	4	0	0	4
Trucks	0	0	0	0
Heavys	0	0	0	0
Totals	4	0	0	

Peds Cross: \times
 South Peds: 0
 South Entering: 4
 South Leg Total: 21

Comments

Ontario Traffic Inc

Morning Peak Diagram

Specified Period

From: 8:30:00
To: 10:30:00

One Hour Peak

From: 8:30:00
To: 9:30:00

Municipality: Cayuga
Site #: 1533100002
Intersection: Brooks Rd & Landfill Access
TFR File #: 1
Count date: 5-Dec-15

Weather conditions:
Person(s) who counted:

**** Non-Signalized Intersection ****

Major Road: Brooks Rd runs N/S


North Leg Total: 10
North Entering: 6
North Peds: 0
Peds Cross: \times

Heavys	0	0	0
Trucks	0	0	0
Cars	6	0	6
Totals	6	0	




Heavys	0
Trucks	0
Cars	4
Totals	4

East Leg Total: 0
East Entering: 0
East Peds: 0
Peds Cross: \times



Brooks Rd




	Cars	Trucks	Heavys	Totals
Upward arrow	0	0	0	0
Downward arrow	0	0	0	0
Rightward arrow	0	0	0	0

Landfill Access



Brooks Rd



Cars	6
Trucks	0
Heavys	0
Totals	6



Cars	4	0	4
Trucks	0	0	0
Heavys	0	0	0
Totals	4	0	

Cars	Trucks	Heavys	Totals
0	0	0	0

Peds Cross: \times
South Peds: 0
South Entering: 4
South Leg Total: 10

Comments

Ontario Traffic Inc

Mid-day Peak Diagram

Specified Period

From: 11:30:00

To: 14:30:00

One Hour Peak

From: 12:15:00

To: 13:15:00

Municipality: Cayuga
Site #: 1533100002
Intersection: Brooks Rd & Landfill Access
TFR File #: 1
Count date: 5-Dec-15

Weather conditions:
Person(s) who counted:

**** Non-Signalized Intersection ****

Major Road: Brooks Rd runs N/S


North Leg Total: 7
 North Entering: 5
 North Peds: 0
 Peds Cross: \times

Heavys	0	0	0
Trucks	0	0	0
Cars	5	0	5
Totals	5	0	




Heavys	0
Trucks	0
Cars	2
Totals	2

East Leg Total: 30
 East Entering: 14
 East Peds: 0
 Peds Cross: \times



Brooks Rd




	Cars	Trucks	Heavys	Totals
Upward arrow	0	0	0	0
Downward arrow	0	14	0	14
Totals	0	14	0	

Landfill Access



Brooks Rd



Cars	5
Trucks	14
Heavys	0
Totals	19



Cars	2	0	2
Trucks	0	16	16
Heavys	0	0	0
Totals	2	16	

Cars	Trucks	Heavys	Totals
0	16	0	16

Peds Cross: \times
 South Peds: 0
 South Entering: 18
 South Leg Total: 37

Comments

Ontario Traffic Inc

Total Count Diagram

Municipality: Cayuga
Site #: 1533100002
Intersection: Brooks Rd & Landfill Access
TFR File #: 1
Count date: 5-Dec-15

Weather conditions:
Person(s) who counted:

**** Non-Signalized Intersection ****

Major Road: Brooks Rd runs N/S


North Leg Total: 29
 North Entering: 18
 North Peds: 0
 Peds Cross: \times

Heavys	0	0	0
Trucks	1	0	1
Cars	17	0	17
Totals	18	0	17




Heavys	0
Trucks	0
Cars	11
Totals	11

East Leg Total: 77
 East Entering: 41
 East Peds: 0
 Peds Cross: \times



Brooks Rd




Cars	0	0	0	0
Trucks	1	40	0	41
Cars	1	40	0	

Landfill Access



Brooks Rd



Cars	0	36	0	36
------	---	----	---	----

Cars	18
Trucks	41
Heavys	0
Totals	59



Cars	11	0	11
Trucks	0	36	36
Heavys	0	0	0
Totals	11	36	36

Peds Cross: \times
 South Peds: 0
 South Entering: 47
 South Leg Total: 106

Comments

Ontario Traffic Inc

Morning Peak Diagram

Specified Period

From: 7:30:00
To: 10:30:00

One Hour Peak

From: 7:30:00
To: 8:30:00

Municipality: Cayuga
Site #: 1533100003
Intersection: Talbot Rd & Brooks Rd
TFR File #: 2
Count date: 7-Dec-15

Weather conditions:
Person(s) who counted:

**** Non-Signalized Intersection ****

Major Road: Talbot Rd runs W/E

North Leg Total: 32
North Entering: 16
North Peds: 0
Peds Cross: \times

Heavys	0	0	0	0
Trucks	0	0	9	9
Cars	3	0	4	7
Totals	3	0	13	



Heavys	0
Trucks	8
Cars	8
Totals	16

East Leg Total: 244
East Entering: 128
East Peds: 0
Peds Cross: \times

Heavys	0
Trucks	15
Cars	102
Totals	117




Brooks Rd


Cars	6	8	0	14
Trucks	99	15	0	114
Heavys	0	0	0	0
Totals	105	23	0	



Talbot Rd



Heavys	0
Trucks	0
Cars	1
Totals	1
Heavys	0
Trucks	10
Cars	93
Totals	103
Heavys	0
Trucks	0
Cars	0
Totals	0
Heavys	0
Trucks	10
Cars	94
Totals	



Talbot Rd



Peds Cross: \times
West Peds: 0
West Entering: 104
West Leg Total: 221

Cars	0
Trucks	0
Heavys	0
Totals	0



Cars	0	1	0	1
Trucks	0	0	0	0
Heavys	0	0	0	0
Totals	0	1	0	



McFarlane Rd

Peds Cross: \times
South Peds: 0
South Entering: 1
South Leg Total: 1

Comments

Ontario Traffic Inc

Mid-day Peak Diagram

Specified Period

From: 11:30:00
To: 13:30:00

One Hour Peak

From: 12:30:00
To: 13:30:00

Municipality: Cayuga
Site #: 1533100003
Intersection: Talbot Rd & Brooks Rd
TFR File #: 2
Count date: 7-Dec-15

Weather conditions:
Person(s) who counted:

**** Non-Signalized Intersection ****

Major Road: Talbot Rd runs W/E

North Leg Total: 29
North Entering: 13
North Peds: 0
Peds Cross: \times

Heavys	0	0	0	0
Trucks	0	0	11	11
Cars	2	0	0	2
Totals	2	0	11	



Heavys	0
Trucks	14
Cars	2
Totals	16

East Leg Total: 245
East Entering: 122
East Peds: 0
Peds Cross: \times

Heavys	0
Trucks	12
Cars	99
Totals	111




Brooks Rd


Cars	1	13	0	14
Trucks	96	12	0	108
Heavys	0	0	0	0
Totals	97	25	0	



Talbot Rd



Heavys	0
Trucks	1
Cars	1
Totals	2
Heavys	0
Trucks	12
Cars	100
Totals	112
Heavys	0
Trucks	0
Cars	0
Totals	0
Heavys	0
Trucks	13
Cars	101
Totals	



Talbot Rd



Peds Cross: \times
West Peds: 0
West Entering: 114
West Leg Total: 225

Cars	0
Trucks	0
Heavys	0
Totals	0



Cars	1	0	0	1
Trucks	0	0	0	0
Heavys	0	0	0	0
Totals	1	0	0	



McFarlane Rd

Cars	100	23	0	123
Trucks				
Heavys				
Totals				

Peds Cross: \times
South Peds: 0
South Entering: 1
South Leg Total: 1

Comments

Ontario Traffic Inc

Afternoon Peak Diagram

Specified Period

From: 14:00:00
To: 16:30:00

One Hour Peak

From: 15:30:00
To: 16:30:00

Municipality: Cayuga
Site #: 1533100003
Intersection: Talbot Rd & Brooks Rd
TFR File #: 2
Count date: 7-Dec-15

Weather conditions:
Person(s) who counted:

**** Non-Signalized Intersection ****

Major Road: Talbot Rd runs W/E

North Leg Total: 28
North Entering: 13
North Peds: 0
Peds Cross: \times

Heavys	0	0	0	0
Trucks	0	0	11	11
Cars	0	0	2	2
Totals	0	0	13	



Heavys	0
Trucks	11
Cars	4
Totals	15

East Leg Total: 335
East Entering: 166
East Peds: 0
Peds Cross: \times

Heavys	0
Trucks	15
Cars	139
Totals	154




Brooks Rd


Cars	2	11	0	13
Trucks	138	15	0	153
Heavys	0	0	0	0
Totals	140	26	0	



Talbot Rd



Heavys	0
Trucks	0
Cars	2
Totals	2
Heavys	0
Trucks	13
Cars	143
Totals	156
Heavys	0
Trucks	0
Cars	2
Totals	2
Heavys	0
Trucks	13
Cars	147
Totals	



Talbot Rd



Peds Cross: \times
West Peds: 0
West Entering: 160
West Leg Total: 314

Cars	2
Trucks	0
Heavys	0
Totals	2



Cars	1	0	0	1
Trucks	0	0	0	0
Heavys	0	0	0	0
Totals	1	0	0	

Peds Cross: \times
South Peds: 0
South Entering: 1
South Leg Total: 3

Comments

Ontario Traffic Inc

Total Count Diagram

Municipality: Cayuga
Site #: 1533100003
Intersection: Talbot Rd & Brooks Rd
TFR File #: 2
Count date: 7-Dec-15

Weather conditions:
Person(s) who counted:

**** Non-Signalized Intersection ****

Major Road: Talbot Rd runs W/E

North Leg Total: 218
 North Entering: 103
 North Peds: 0
 Peds Cross: \times

Heavys	0	0	0	0
Trucks	4	0	75	79
Cars	13	0	11	24
Totals	17	0	86	



Heavys	0
Trucks	86
Cars	29
Totals	115


East Leg Total: 1892
 East Entering: 928
 East Peds: 0
 Peds Cross: \times

Heavys	0	Trucks	113	Cars	739	Totals	852
--------	---	--------	-----	------	-----	--------	-----




Brooks Rd


Cars	18	Trucks	81	Heavys	0	Totals	99
Cars	720	Trucks	109	Heavys	0	Totals	829
Cars	0	Trucks	0	Heavys	0	Totals	0
Cars	738	Trucks	190	Heavys	0	Totals	



Talbot Rd



Heavys	0	Trucks	5	Cars	10	Totals	15
Heavys	0	Trucks	89	Cars	787	Totals	876
Heavys	0	Trucks	0	Cars	5	Totals	5
Heavys	0	Trucks	94	Cars	802	Totals	



Talbot Rd



Peds Cross: \times
 West Peds: 0
 West Entering: 896
 West Leg Total: 1748

Cars	5
Trucks	0
Heavys	0
Totals	5



McFarlane Rd

Cars	6	1	2	9
Trucks	0	0	0	0
Heavys	0	0	0	0
Totals	6	1	2	



Peds Cross: \times
 South Peds: 0
 South Entering: 9
 South Leg Total: 14

Comments

Ontario Traffic Inc

Morning Peak Diagram

Specified Period

From: 7:30:00
To: 10:30:00

One Hour Peak

From: 7:30:00
To: 8:30:00

Municipality: Cayuga
Site #: 1533100004
Intersection: Brooks Rd & Landfill Access
TFR File #: 2
Count date: 7-Dec-15

Weather conditions:
Person(s) who counted:

**** Non-Signalized Intersection ****

Major Road: Brooks Rd runs N/S


North Leg Total: 7
North Entering: 5
North Peds: 0
Peds Cross: \times

Heavys	0	0	0
Trucks	0	0	0
Cars	5	0	5
Totals	5	0	




Heavys	0
Trucks	0
Cars	2
Totals	2

East Leg Total: 23
East Entering: 11
East Peds: 0
Peds Cross: \times



Brooks Rd




	Cars	Trucks	Heavys	Totals
	0	0	0	0
	3	8	0	11
	3	8	0	

Landfill Access



	Cars	Trucks	Heavys	Totals
	3	9	0	12

Brooks Rd



Cars	8
Trucks	8
Heavys	0
Totals	16



Cars	2	3	5
Trucks	0	9	9
Heavys	0	0	0
Totals	2	12	

Peds Cross: \times
South Peds: 0
South Entering: 14
South Leg Total: 30

Comments

Ontario Traffic Inc

Mid-day Peak Diagram

Specified Period

From: 11:30:00
To: 13:30:00

One Hour Peak

From: 12:30:00
To: 13:30:00

Municipality: Cayuga
Site #: 1533100004
Intersection: Brooks Rd & Landfill Access
TFR File #: 2
Count date: 7-Dec-15

Weather conditions:
Person(s) who counted:

**** Non-Signalized Intersection ****

Major Road: Brooks Rd runs N/S


North Leg Total: 8
North Entering: 3
North Peds: 0
Peds Cross: \times

Heavys	0	0	0
Trucks	0	0	0
Cars	3	0	3
Totals	3	0	




Heavys	0
Trucks	1
Cars	4
Totals	5

East Leg Total: 25
East Entering: 13
East Peds: 0
Peds Cross: \times



Brooks Rd




	Cars	Trucks	Heavys	Totals
	0	0	0	0
	1	12	0	13
	1	12	0	

Landfill Access



Brooks Rd



Cars	4	Cars	4	0	4
Trucks	12	Trucks	1	12	13
Heavys	0	Heavys	0	0	0
Totals	16	Totals	5	12	



Cars	Trucks	Heavys	Totals
0	12	0	12

Peds Cross: \times
South Peds: 0
South Entering: 17
South Leg Total: 33

Comments

Ontario Traffic Inc

Afternoon Peak Diagram

Specified Period

From: 14:00:00

To: 16:30:00

One Hour Peak

From: 15:15:00

To: 16:15:00

Municipality: Cayuga
Site #: 1533100004
Intersection: Brooks Rd & Landfill Access
TFR File #: 2
Count date: 7-Dec-15

Weather conditions:
Person(s) who counted:

**** Non-Signalized Intersection ****

Major Road: Brooks Rd runs N/S


North Leg Total: 5
 North Entering: 1
 North Peds: 0
 Peds Cross: \times

Heavys	0	0	0
Trucks	0	0	0
Cars	1	0	1
Totals	1	0	




Heavys	0
Trucks	0
Cars	4
Totals	4

East Leg Total: 23
 East Entering: 13
 East Peds: 0
 Peds Cross: \times



Brooks Rd




	Cars	Trucks	Heavys	Totals
Upward arrow	1	0	0	1
Downward arrow	1	11	0	12
Totals	2	11	0	

Landfill Access



Brooks Rd



Cars	2
Trucks	11
Heavys	0
Totals	13



Cars	3	0	3
Trucks	0	10	10
Heavys	0	0	0
Totals	3	10	

Cars	Trucks	Heavys	Totals
0	10	0	10

Peds Cross: \times
 South Peds: 0
 South Entering: 13
 South Leg Total: 26

Comments

Ontario Traffic Inc

Total Count Diagram

Municipality: Cayuga
Site #: 1533100004
Intersection: Brooks Rd & Landfill Access
TFR File #: 2
Count date: 7-Dec-15

Weather conditions:
Person(s) who counted:

**** Non-Signalized Intersection ****

Major Road: Brooks Rd runs N/S


North Leg Total: 43
 North Entering: 23
 North Peds: 1
 Peds Cross: \times

Heavys	0	0	0
Trucks	1	0	1
Cars	22	0	22
Totals	23	0	23




Heavys	0
Trucks	1
Cars	19
Totals	20

East Leg Total: 163
 East Entering: 85
 East Peds: 0
 Peds Cross: \times



Brooks Rd




	Cars	Trucks	Heavys	Totals
	1	0	0	1
	7	77	0	84
	8	77	0	

Landfill Access



Brooks Rd



Cars	29
Trucks	78
Heavys	0
Totals	107



Cars	18	4	22
Trucks	1	74	75
Heavys	0	0	0
Totals	19	78	97

















Peds Cross: \times
 South Peds: 0
 South Entering: 97
 South Leg Total: 204

Comments

Synchro Reports

Lanes, Volumes, Timings
 1: McFarlane Road/Brooks Road & Talbot Road

2022 Existing Traffic
 Weekday AM Peak Hour

















												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	2	118	0	0	130	30	0	2	0	27	0	6
Future Volume (vph)	2	118	0	0	130	30	0	2	0	27	0	6
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Fr _t					0.974							0.974
Fl _t Protected		0.999										0.961
Satd. Flow (prot)	0	1882	0	0	1834	0	0	1883	0	0	1763	0
Fl _t Permitted		0.999										0.961
Satd. Flow (perm)	0	1882	0	0	1834	0	0	1883	0	0	1763	0
Link Speed (k/h)		48			48			48			48	
Link Distance (m)		582.0			708.0			1694.7			1063.5	
Travel Time (s)		43.7			53.1			127.1			79.8	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	2	128	0	0	141	33	0	2	0	29	0	7
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	130	0	0	174	0	0	2	0	0	36	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(m)		0.0			0.0			0.0			0.0	
Link Offset(m)		0.0			0.0			0.0			0.0	
Crosswalk Width(m)		1.6			1.6			1.6			1.6	
Two way Left Turn Lane												
Headway Factor	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99
Turning Speed (k/h)	24		14	24		14	24		14	24		14
Sign Control		Free			Free			Stop			Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	23.9%
Analysis Period (min)	15
	ICU Level of Service A










HCM Unsignalized Intersection Capacity Analysis
 1: McFarlane Road/Brooks Road & Talbot Road

2022 Existing Traffic
 Weekday AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	2	118	0	0	130	30	0	2	0	27	0	6
Future Volume (Veh/h)	2	118	0	0	130	30	0	2	0	27	0	6
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	2	128	0	0	141	33	0	2	0	29	0	7
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type		None			None							
Median storage (veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	174			128			296	306	128	290	290	158
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	174			128			296	306	128	290	290	158
tC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	100			100			100	100	100	96	100	99
cM capacity (veh/h)	1403			1458			650	607	922	659	620	888
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	130	174	2	36								
Volume Left	2	0	0	29								
Volume Right	0	33	0	7								
cSH	1403	1458	607	694								
Volume to Capacity	0.00	0.00	0.00	0.05								
Queue Length 95th (m)	0.0	0.0	0.1	1.2								
Control Delay (s)	0.1	0.0	11.0	10.5								
Lane LOS	A		B	B								
Approach Delay (s)	0.1	0.0	11.0	10.5								
Approach LOS			B	B								
Intersection Summary												
Average Delay			1.2									
Intersection Capacity Utilization			23.9%		ICU Level of Service				A			
Analysis Period (min)			15									

Lanes, Volumes, Timings
2: Brooks Road & Landfill Access










2022 Existing Traffic
Weekday AM Peak Hour

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	27	0	2	28	0	5
Future Volume (vph)	27	0	2	28	0	5
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt	0.873					
Flt Protected	0.950					
Satd. Flow (prot)	1789	0	1644	0	0	1883
Flt Permitted	0.950					
Satd. Flow (perm)	1789	0	1644	0	0	1883
Link Speed (k/h)	48	48		48		
Link Distance (m)	758.3	1063.5		423.8		
Travel Time (s)	56.9	79.8		31.8		
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	29	0	2	30	0	5
Shared Lane Traffic (%)						
Lane Group Flow (vph)	29	0	32	0	0	5
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Right	Left	Left
Median Width(m)	3.7	0.0		0.0		
Link Offset(m)	0.0	0.0		0.0		
Crosswalk Width(m)	1.6	1.6		1.6		
Two way Left Turn Lane						
Headway Factor	0.99	0.99	0.99	0.99	0.99	0.99
Turning Speed (k/h)	24	14		14	24	
Sign Control	Stop	Free		Free		
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	13.3%			ICU Level of Service A		
Analysis Period (min)	15					

HCM Unsignalized Intersection Capacity Analysis

















2: Brooks Road & Landfill Access

2022 Existing Traffic
Weekday AM Peak Hour

						
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (veh/h)	27	0	2	28	0	5
Future Volume (Veh/h)	27	0	2	28	0	5
Sign Control	Stop		Free		Free	
Grade	0%		0%		0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	29	0	2	30	0	5
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage (veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	22	17			32	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	22	17			32	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	97	100			100	
cM capacity (veh/h)	995	1062			1580	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	29	32	5			
Volume Left	29	0	0			
Volume Right	0	30	0			
cSH	995	1700	1580			
Volume to Capacity	0.03	0.02	0.00			
Queue Length 95th (m)	0.7	0.0	0.0			
Control Delay (s)	8.7	0.0	0.0			
Lane LOS	A					
Approach Delay (s)	8.7	0.0	0.0			
Approach LOS	A					
Intersection Summary						
Average Delay			3.8			
Intersection Capacity Utilization			13.3%	ICU Level of Service	A	
Analysis Period (min)			15			

















Lanes, Volumes, Timings
 1: McFarlane Road/Brooks Road & Talbot Road

2022 Existing Traffic
 Weekday Mid-day Peak Hour

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	4	128	0	0	124	30	1	0	0	26	0	4
Future Volume (vph)	4	128	0	0	124	30	1	0	0	26	0	4
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt					0.973							0.983
Flt Protected		0.999						0.950				0.958
Satd. Flow (prot)	0	1882	0	0	1833	0	0	1789	0	0	1774	0
Flt Permitted		0.999						0.950				0.958
Satd. Flow (perm)	0	1882	0	0	1833	0	0	1789	0	0	1774	0
Link Speed (k/h)		48			48			48			48	
Link Distance (m)		582.0			708.0			1694.7			1063.5	
Travel Time (s)		43.7			53.1			127.1			79.8	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	4	139	0	0	135	33	1	0	0	28	0	4
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	143	0	0	168	0	0	1	0	0	32	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(m)		0.0			0.0			0.0			0.0	
Link Offset(m)		0.0			0.0			0.0			0.0	
Crosswalk Width(m)		1.6			1.6			1.6			1.6	
Two way Left Turn Lane												
Headway Factor	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99
Turning Speed (k/h)	24		14	24		14	24		14	24		14
Sign Control		Free			Free			Stop			Stop	
Intersection Summary												
Area Type:	Other											
Control Type:	Unsignalized											
Intersection Capacity Utilization	20.0%						ICU Level of Service A					
Analysis Period (min)	15											










HCM Unsignalized Intersection Capacity Analysis
 1: McFarlane Road/Brooks Road & Talbot Road

2022 Existing Traffic
 Weekday Mid-day Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	4	128	0	0	124	30	1	0	0	26	0	4
Future Volume (Veh/h)	4	128	0	0	124	30	1	0	0	26	0	4
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	4	139	0	0	135	33	1	0	0	28	0	4
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type		None			None							
Median storage (veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	168			139			302	315	139	298	298	152
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	168			139			302	315	139	298	298	152
tC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	100			100			100	100	100	96	100	100
cM capacity (veh/h)	1410			1445			646	599	909	652	612	895
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	143	168	1	32								
Volume Left	4	0	1	28								
Volume Right	0	33	0	4								
cSH	1410	1445	646	675								
Volume to Capacity	0.00	0.00	0.00	0.05								
Queue Length 95th (m)	0.1	0.0	0.0	1.1								
Control Delay (s)	0.2	0.0	10.6	10.6								
Lane LOS	A		B	B								
Approach Delay (s)	0.2	0.0	10.6	10.6								
Approach LOS			B	B								
Intersection Summary												
Average Delay			1.1									
Intersection Capacity Utilization			20.0%		ICU Level of Service				A			
Analysis Period (min)			15									

Lanes, Volumes, Timings
2: Brooks Road & Landfill Access










2022 Existing Traffic
Weekday Mid-day Peak Hour

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	29	0	5	28	0	2
Future Volume (vph)	29	0	5	28	0	2
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt	0.884					
Flt Protected	0.950					
Satd. Flow (prot)	1789	0	1665	0	0	1883
Flt Permitted	0.950					
Satd. Flow (perm)	1789	0	1665	0	0	1883
Link Speed (k/h)	48	48		48		
Link Distance (m)	758.3	1063.5		423.8		
Travel Time (s)	56.9	79.8		31.8		
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	32	0	5	30	0	2
Shared Lane Traffic (%)						
Lane Group Flow (vph)	32	0	35	0	0	2
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Right	Left	Left
Median Width(m)	3.7	0.0		0.0		
Link Offset(m)	0.0	0.0		0.0		
Crosswalk Width(m)	1.6	1.6		1.6		
Two way Left Turn Lane						
Headway Factor	0.99	0.99	0.99	0.99	0.99	0.99
Turning Speed (k/h)	24	14		14	24	
Sign Control	Stop		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	13.3%			ICU Level of Service A		
Analysis Period (min)	15					

HCM Unsignalized Intersection Capacity Analysis

















2: Brooks Road & Landfill Access

2022 Existing Traffic
Weekday Mid-day Peak Hour

						
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (veh/h)	29	0	5	28	0	2
Future Volume (Veh/h)	29	0	5	28	0	2
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	32	0	5	30	0	2
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage (veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	22	20			35	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	22	20			35	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	97	100			100	
cM capacity (veh/h)	995	1058			1576	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	32	35	2			
Volume Left	32	0	0			
Volume Right	0	30	0			
cSH	995	1700	1576			
Volume to Capacity	0.03	0.02	0.00			
Queue Length 95th (m)	0.8	0.0	0.0			
Control Delay (s)	8.7	0.0	0.0			
Lane LOS	A					
Approach Delay (s)	8.7	0.0	0.0			
Approach LOS	A					
Intersection Summary						
Average Delay			4.1			
Intersection Capacity Utilization			13.3%	ICU Level of Service	A	
Analysis Period (min)			15			

















Lanes, Volumes, Timings
 1: McFarlane Road/Brooks Road & Talbot Road

2022 Existing Traffic
 Weekday PM Peak Hour

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	4	174	2	0	175	28	1	0	0	29	0	0
Future Volume (vph)	4	174	2	0	175	28	1	0	0	29	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Fr _t		0.999			0.982							
Fl _t Protected		0.999						0.950			0.950	
Satd. Flow (prot)	0	1880	0	0	1850	0	0	1789	0	0	1789	0
Fl _t Permitted		0.999						0.950			0.950	
Satd. Flow (perm)	0	1880	0	0	1850	0	0	1789	0	0	1789	0
Link Speed (k/h)		48			48			48			48	
Link Distance (m)		582.0			708.0			1694.7			1063.5	
Travel Time (s)		43.7			53.1			127.1			79.8	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	4	189	2	0	190	30	1	0	0	32	0	0
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	195	0	0	220	0	0	1	0	0	32	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(m)		0.0			0.0			0.0			0.0	
Link Offset(m)		0.0			0.0			0.0			0.0	
Crosswalk Width(m)		1.6			1.6			1.6			1.6	
Two way Left Turn Lane												
Headway Factor	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99
Turning Speed (k/h)	24		14	24		14	24		14	24		14
Sign Control		Free			Free			Stop			Stop	
Intersection Summary												
Area Type:	Other											
Control Type:	Unsignalized											
Intersection Capacity Utilization	22.5%						ICU Level of Service A					
Analysis Period (min)	15											










HCM Unsignalized Intersection Capacity Analysis
 1: McFarlane Road/Brooks Road & Talbot Road

2022 Existing Traffic
 Weekday PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	4	174	2	0	175	28	1	0	0	29	0	0
Future Volume (Veh/h)	4	174	2	0	175	28	1	0	0	29	0	0
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	4	189	2	0	190	30	1	0	0	32	0	0
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type		None			None							
Median storage (veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	220			191			403	418	190	403	404	205
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	220			191			403	418	190	403	404	205
tC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	100			100			100	100	100	94	100	100
cM capacity (veh/h)	1349			1383			557	524	852	557	534	836
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	195	220	1	32								
Volume Left	4	0	1	32								
Volume Right	2	30	0	0								
cSH	1349	1383	557	557								
Volume to Capacity	0.00	0.00	0.00	0.06								
Queue Length 95th (m)	0.1	0.0	0.0	1.4								
Control Delay (s)	0.2	0.0	11.5	11.9								
Lane LOS	A		B	B								
Approach Delay (s)	0.2	0.0	11.5	11.9								
Approach LOS			B	B								
Intersection Summary												
Average Delay			1.0									
Intersection Capacity Utilization			22.5%		ICU Level of Service				A			
Analysis Period (min)			15									

Lanes, Volumes, Timings
2: Brooks Road & Landfill Access










2022 Existing Traffic
Weekday PM Peak Hour

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	27	2	3	26	0	1
Future Volume (vph)	27	2	3	26	0	1
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt	0.991		0.878			
Flt Protected	0.955					
Satd. Flow (prot)	1782	0	1654	0	0	1883
Flt Permitted	0.955					
Satd. Flow (perm)	1782	0	1654	0	0	1883
Link Speed (k/h)	48		48			48
Link Distance (m)	758.3		1063.5			423.8
Travel Time (s)	56.9		79.8			31.8
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	29	2	3	28	0	1
Shared Lane Traffic (%)						
Lane Group Flow (vph)	31	0	31	0	0	1
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Right	Left	Left
Median Width(m)	3.7		0.0			0.0
Link Offset(m)	0.0		0.0			0.0
Crosswalk Width(m)	1.6		1.6			1.6
Two way Left Turn Lane						
Headway Factor	0.99	0.99	0.99	0.99	0.99	0.99
Turning Speed (k/h)	24	14		14	24	
Sign Control	Stop		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	13.3%			ICU Level of Service A		
Analysis Period (min)	15					

HCM Unsignalized Intersection Capacity Analysis

2: Brooks Road & Landfill Access

2022 Existing Traffic
Weekday PM Peak Hour

						
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (veh/h)	27	2	3	26	0	1
Future Volume (Veh/h)	27	2	3	26	0	1
Sign Control	Stop		Free		Free	
Grade	0%		0%		0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	29	2	3	28	0	1
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage (veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	18	17			31	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	18	17			31	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	97	100			100	
cM capacity (veh/h)	1000	1062			1582	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	31	31	1			
Volume Left	29	0	0			
Volume Right	2	28	0			
cSH	1004	1700	1582			
Volume to Capacity	0.03	0.02	0.00			
Queue Length 95th (m)	0.7	0.0	0.0			
Control Delay (s)	8.7	0.0	0.0			
Lane LOS	A					
Approach Delay (s)	8.7	0.0	0.0			
Approach LOS	A					
Intersection Summary						
Average Delay			4.3			
Intersection Capacity Utilization			13.3%		ICU Level of Service	A
Analysis Period (min)			15			

















Lanes, Volumes, Timings
 1: McFarlane Road/Brooks Road & Talbot Road

2022 Existing Traffic
 Saturday Mid-day Peak Hour

Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	6	181	3	0	179	30	0	0	0	28	0	8
Future Volume (vph)	6	181	3	0	179	30	0	0	0	28	0	8
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Fr _t		0.998			0.980							0.969
Fl _t Protected		0.998										0.963
Satd. Flow (prot)	0	1876	0	0	1846	0	0	1883	0	0	1758	0
Fl _t Permitted		0.998										0.963
Satd. Flow (perm)	0	1876	0	0	1846	0	0	1883	0	0	1758	0
Link Speed (k/h)		48			48			48			48	
Link Distance (m)		582.0			708.0			1694.7			1063.5	
Travel Time (s)		43.7			53.1			127.1			79.8	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	7	197	3	0	195	33	0	0	0	30	0	9
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	207	0	0	228	0	0	0	0	0	39	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(m)		0.0			0.0			0.0			0.0	
Link Offset(m)		0.0			0.0			0.0			0.0	
Crosswalk Width(m)		1.6			1.6			1.6			1.6	
Two way Left Turn Lane												
Headway Factor	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99
Turning Speed (k/h)	24		14	24		14	24		14	24		14
Sign Control		Free			Free			Stop			Stop	
Intersection Summary												
Area Type:	Other											
Control Type:	Unsignalized											
Intersection Capacity Utilization	24.6%						ICU Level of Service A					
Analysis Period (min)	15											










HCM Unsignalized Intersection Capacity Analysis
 1: McFarlane Road/Brooks Road & Talbot Road

2022 Existing Traffic
 Saturday Mid-day Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	6	181	3	0	179	30	0	0	0	28	0	8
Future Volume (Veh/h)	6	181	3	0	179	30	0	0	0	28	0	8
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	7	197	3	0	195	33	0	0	0	30	0	9
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type		None			None							
Median storage (veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	228			200			433	440	198	424	426	212
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	228			200			433	440	198	424	426	212
tC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	99			100			100	100	100	94	100	99
cM capacity (veh/h)	1340			1372			525	508	843	538	518	829
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	207	228	0	39								
Volume Left	7	0	0	30								
Volume Right	3	33	0	9								
cSH	1340	1372	1700	586								
Volume to Capacity	0.01	0.00	0.00	0.07								
Queue Length 95th (m)	0.1	0.0	0.0	1.6								
Control Delay (s)	0.3	0.0	0.0	11.6								
Lane LOS	A		A	B								
Approach Delay (s)	0.3	0.0	0.0	11.6								
Approach LOS			A	B								
Intersection Summary												
Average Delay			1.1									
Intersection Capacity Utilization			24.6%		ICU Level of Service				A			
Analysis Period (min)			15									










Lanes, Volumes, Timings
2: Brooks Road & Landfill Access

2022 Existing Traffic
Saturday Mid-day Peak Hour

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	30	0	2	32	0	5
Future Volume (vph)	30	0	2	32	0	5
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt	0.872					
Flt Protected	0.950					
Satd. Flow (prot)	1789	0	1642	0	0	1883
Flt Permitted	0.950					
Satd. Flow (perm)	1789	0	1642	0	0	1883
Link Speed (k/h)	48	48		48		
Link Distance (m)	758.3	1063.5		423.8		
Travel Time (s)	56.9	79.8		31.8		
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	33	0	2	35	0	5
Shared Lane Traffic (%)						
Lane Group Flow (vph)	33	0	37	0	0	5
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Right	Left	Left
Median Width(m)	3.7	0.0		0.0		
Link Offset(m)	0.0	0.0		0.0		
Crosswalk Width(m)	1.6	1.6		1.6		
Two way Left Turn Lane						
Headway Factor	0.99	0.99	0.99	0.99	0.99	0.99
Turning Speed (k/h)	24	14		14	24	
Sign Control	Stop		Free			Free
Intersection Summary						
Area Type:	Other					
Control Type:	Unsignalized					
Intersection Capacity Utilization	13.3%			ICU Level of Service A		
Analysis Period (min)	15					

HCM Unsignalized Intersection Capacity Analysis
2: Brooks Road & Landfill Access

2022 Existing Traffic
Saturday Mid-day Peak Hour

















						
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (veh/h)	30	0	2	32	0	5
Future Volume (Veh/h)	30	0	2	32	0	5
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	33	0	2	35	0	5
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	24	20			37	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	24	20			37	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	97	100			100	
cM capacity (veh/h)	991	1058			1574	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	33	37	5			
Volume Left	33	0	0			
Volume Right	0	35	0			
cSH	991	1700	1574			
Volume to Capacity	0.03	0.02	0.00			
Queue Length 95th (m)	0.8	0.0	0.0			
Control Delay (s)	8.8	0.0	0.0			
Lane LOS	A					
Approach Delay (s)	8.8	0.0	0.0			
Approach LOS	A					
Intersection Summary						
Average Delay			3.9			
Intersection Capacity Utilization		13.3%		ICU Level of Service		A
Analysis Period (min)			15			

2026 Reports

HCM Unsignalized Intersection Capacity Analysis

1: McFarlane Road/Brooks Road & Talbot Road

11/09/2023

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	2	128	0	0	142	31	0	2	0	29	0	7
Future Volume (Veh/h)	2	128	0	0	142	31	0	2	0	29	0	7
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	2	139	0	0	154	34	0	2	0	32	0	8
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type		None			None							
Median storage (veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	188			139			322	331	139	315	314	171
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	188			139			322	331	139	315	314	171
tC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	100			100			100	100	100	95	100	99
cM capacity (veh/h)	1386			1445			624	588	909	635	601	873
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	141	188	2	40								
Volume Left	2	0	0	32								
Volume Right	0	34	0	8								
cSH	1386	1445	588	672								
Volume to Capacity	0.00	0.00	0.00	0.06								
Queue Length 95th (m)	0.0	0.0	0.1	1.4								
Control Delay (s)	0.1	0.0	11.1	10.7								
Lane LOS	A		B	B								
Approach Delay (s)	0.1	0.0	11.1	10.7								
Approach LOS			B	B								
Intersection Summary												
Average Delay			1.3									
Intersection Capacity Utilization			24.7%		ICU Level of Service				A			
Analysis Period (min)			15									

HCM Unsignalized Intersection Capacity Analysis

2: Brooks Road & Landfill Access

11/09/2023



















Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (veh/h)	27	0	2	28	0	6
Future Volume (Veh/h)	27	0	2	28	0	6
Sign Control	Stop		Free		Free	
Grade	0%		0%		0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	29	0	2	30	0	7
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	24	17			32	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	24	17			32	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	97	100			100	
cM capacity (veh/h)	992	1062			1580	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	29	32	7			
Volume Left	29	0	0			
Volume Right	0	30	0			
cSH	992	1700	1580			
Volume to Capacity	0.03	0.02	0.00			
Queue Length 95th (m)	0.7	0.0	0.0			
Control Delay (s)	8.7	0.0	0.0			
Lane LOS	A					
Approach Delay (s)	8.7	0.0	0.0			
Approach LOS	A					
Intersection Summary						
Average Delay			3.7			
Intersection Capacity Utilization			13.3%	ICU Level of Service	A	
Analysis Period (min)			15			

HCM Unsignalized Intersection Capacity Analysis

1: McFarlane Road/Brooks Road & Talbot Road

11/09/2023

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	4	139	0	0	134	31	1	0	0	28	0	4
Future Volume (Veh/h)	4	139	0	0	134	31	1	0	0	28	0	4
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	4	151	0	0	146	34	1	0	0	30	0	4
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type		None			None							
Median storage (veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	180			151			326	339	151	322	322	163
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	180			151			326	339	151	322	322	163
tC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	100			100			100	100	100	95	100	100
cM capacity (veh/h)	1396			1430			623	581	895	630	594	882
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	155	180	1	34								
Volume Left	4	0	1	30								
Volume Right	0	34	0	4								
cSH	1396	1430	623	651								
Volume to Capacity	0.00	0.00	0.00	0.05								
Queue Length 95th (m)	0.1	0.0	0.0	1.3								
Control Delay (s)	0.2	0.0	10.8	10.8								
Lane LOS	A		B	B								
Approach Delay (s)	0.2	0.0	10.8	10.8								
Approach LOS			B	B								
Intersection Summary												
Average Delay			1.1									
Intersection Capacity Utilization			20.5%		ICU Level of Service				A			
Analysis Period (min)			15									

HCM Unsignalized Intersection Capacity Analysis

2: Brooks Road & Landfill Access

11/09/2023



















Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (veh/h)	29	0	6	28	0	2
Future Volume (Veh/h)	29	0	6	28	0	2
Sign Control	Stop		Free		Free	
Grade	0%		0%		0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	32	0	7	30	0	2
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage (veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	24	22			37	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	24	22			37	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	97	100			100	
cM capacity (veh/h)	992	1055			1574	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	32	37	2			
Volume Left	32	0	0			
Volume Right	0	30	0			
cSH	992	1700	1574			
Volume to Capacity	0.03	0.02	0.00			
Queue Length 95th (m)	0.8	0.0	0.0			
Control Delay (s)	8.8	0.0	0.0			
Lane LOS	A					
Approach Delay (s)	8.8	0.0	0.0			
Approach LOS	A					
Intersection Summary						
Average Delay			3.9			
Intersection Capacity Utilization			13.3%		ICU Level of Service	A
Analysis Period (min)			15			

HCM Unsignalized Intersection Capacity Analysis

1: McFarlane Road/Brooks Road & Talbot Road

11/09/2023

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	4	189	2	0	190	30	1	0	0	31	0	0
Future Volume (Veh/h)	4	189	2	0	190	30	1	0	0	31	0	0
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	4	205	2	0	207	33	1	0	0	34	0	0
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type		None			None							
Median storage (veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	240			207			438	454	206	438	438	224
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	240			207			438	454	206	438	438	224
tC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	100			100			100	100	100	94	100	100
cM capacity (veh/h)	1327			1364			528	500	835	528	511	816
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	211	240	1	34								
Volume Left	4	0	1	34								
Volume Right	2	33	0	0								
cSH	1327	1364	528	528								
Volume to Capacity	0.00	0.00	0.00	0.06								
Queue Length 95th (m)	0.1	0.0	0.0	1.6								
Control Delay (s)	0.2	0.0	11.8	12.3								
Lane LOS	A		B	B								
Approach Delay (s)	0.2	0.0	11.8	12.3								
Approach LOS			B	B								
Intersection Summary												
Average Delay			1.0									
Intersection Capacity Utilization			23.3%		ICU Level of Service				A			
Analysis Period (min)			15									

HCM Unsignalized Intersection Capacity Analysis

2: Brooks Road & Landfill Access

11/09/2023



















Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (veh/h)	27	2	4	26	0	1
Future Volume (Veh/h)	27	2	4	26	0	1
Sign Control	Stop		Free		Free	
Grade	0%		0%		0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	29	2	4	28	0	1
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage (veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	19	18			32	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	19	18			32	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	97	100			100	
cM capacity (veh/h)	998	1061			1580	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	31	32	1			
Volume Left	29	0	0			
Volume Right	2	28	0			
cSH	1002	1700	1580			
Volume to Capacity	0.03	0.02	0.00			
Queue Length 95th (m)	0.7	0.0	0.0			
Control Delay (s)	8.7	0.0	0.0			
Lane LOS	A					
Approach Delay (s)	8.7	0.0	0.0			
Approach LOS	A					
Intersection Summary						
Average Delay			4.2			
Intersection Capacity Utilization			13.3%	ICU Level of Service	A	
Analysis Period (min)			15			

HCM Unsignalized Intersection Capacity Analysis

1: McFarlane Road/Brooks Road & Talbot Road

11/09/2023

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	7	196	4	0	194	32	0	0	0	29	0	9
Future Volume (Veh/h)	7	196	4	0	194	32	0	0	0	29	0	9
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	8	213	4	0	211	35	0	0	0	32	0	10
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type		None			None							
Median storage (veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	246			217			470	477	215	460	462	228
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	246			217			470	477	215	460	462	228
tC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	99			100			100	100	100	94	100	99
cM capacity (veh/h)	1320			1353			496	484	825	510	494	811
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	225	246	0	42								
Volume Left	8	0	0	32								
Volume Right	4	35	0	10								
cSH	1320	1353	1700	559								
Volume to Capacity	0.01	0.00	0.00	0.08								
Queue Length 95th (m)	0.1	0.0	0.0	1.8								
Control Delay (s)	0.3	0.0	0.0	12.0								
Lane LOS	A		A	B								
Approach Delay (s)	0.3	0.0	0.0	12.0								
Approach LOS			A	B								
Intersection Summary												
Average Delay			1.1									
Intersection Capacity Utilization			26.2%		ICU Level of Service				A			
Analysis Period (min)			15									

HCM Unsignalized Intersection Capacity Analysis

2: Brooks Road & Landfill Access

11/09/2023



Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (veh/h)	30	0	2	32	0	6
Future Volume (Veh/h)	30	0	2	32	0	6
Sign Control	Stop		Free		Free	
Grade	0%		0%		0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	33	0	2	35	0	7
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	26	20			37	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	26	20			37	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	97	100			100	
cM capacity (veh/h)	989	1058			1574	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	33	37	7			
Volume Left	33	0	0			
Volume Right	0	35	0			
cSH	989	1700	1574			
Volume to Capacity	0.03	0.02	0.00			
Queue Length 95th (m)	0.8	0.0	0.0			
Control Delay (s)	8.8	0.0	0.0			
Lane LOS	A					
Approach Delay (s)	8.8	0.0	0.0			
Approach LOS	A					
Intersection Summary						
Average Delay			3.8			
Intersection Capacity Utilization			13.3%	ICU Level of Service	A	
Analysis Period (min)			15			